




1st ANGLE  
PROJECTION



1	Apr.17.2021	Euro Chlor spec was GEST 06/318; ITP was HMVBS06318;		Liubo	Ludovic
Rev	Date	Description	ECN	Initiated by	Approved by



REF	DESCRIPTION	MATERIAL
1	BODY	ASTM A352 LCC+STELLITE 21
2	BONNET	ASTM A350 LF2
4	BODY/BONNET GASKET	GYLON 3510
11A	DISC	316Ti(1.4571)+STELLITE 6
12	DISC NUT	UNS S43100
13	DISC LOCK WASHER	TYPE 316
20	PACKING RING	PURE PTFE
21	PACKING GLAND	ASTM A351 CF8M
24	GLAND SCRAPER BUSH	PTFE
25	BELLOWS	UNS N10276(2.4819)
30	STEM	UNS S31803
32	YOKE FLANGE	CS AISI 1035
34	YOKE SLEEVE	A439 GRADE D2
35	ANTI ROTATION BRIDGE	CS AISI 1035
36	PILLAR	CS AISI 1035
37	HANDWHEEL	SG IRON BS.EN 1563 EN-GJS-420-12
38	HANDWHEEL LOCKNUT	CS AISI 1035
60	KEY	CS AISI 1025
61	STUD	A320 L7M XYLAN 1424
62	STUD	A320 L7M XYLAN 1424
63	LOCK NUT	A4-70
64	NUT	A320 L7M XYLAN 1424
65	NUT	A320 L7M XYLAN 1424
66	WASHER	CS AISI 1020
67	DOG POINT SCREW	TYPE 316
68	SET SCREW	TYPE 316
69	LUBRICATOR	A570 GR.A
70	WASHER	SS 316
71	NUT	CS AISI 1035 NYLOCK
50	NAME PLATE	TYPE 316
73	NEEDLE ROLLER THRUST BEARING	
74	THRUST WASHER	

Notes:

1. Designed generally in accordance with Euro Chlor GEST 17/492  
Globe Valves Bellow Sealed for Use on Liquid Chlorine. Also conforms to the requirements of The Chlorine Institute's Pamphlet 6-latest edition.
2. Integral weld deposited seat Stellite 21 minimum hardness value HB300 (HRC32 equivalent).
3. Applicable Inspection and Test plan ITP HMVBS17492.
4. Each valve dried in an oven at a minimum of 120°C for at least 3 hours and fitted with gaskets and metal blanking flanges, which have a silica gel satchet attached to their inner face.
5. All lubricants used are chlorine compatible chlorofluorinated.
6. Fitted with stainless steel Tag "CLEANED FOR CHLORINE SERVICE".
7. Valve to be CE marked. Declaration of Conformity HMV\_CE\_002.

Weight: 130kg

MAX INTERNAL RADII 0.5 EXCEPT AS STATED MACHINING TOLERANCES UNLESS OTHERWISE STATED						
to3	3 to6	6 to10	10 to18	18 to30	30 to50	50 to80
±0.07	±0.09	±0.11	±0.14	±0.17	±0.20	±0.23
80 to120	120 to180	180 to250	250 to315	315 to400	400 to500	500 to630
±0.27	±0.32	±0.36	±0.41	±0.45	±0.49	±0.55
SURFACE ROUGHNESS ✓ EXCEPT WHERE OTHERWISE STATED						
AS PRODUCED BY COMMON PRODUCTION PROCESSES						
ROUGH TURN			FINE TURNING			
TURNING OR MILLING						

DO NOT SCALE DRAWING.  
ALL DIMENSIONS IN MILLIMETRES(mm)/  
UNLESS OTHERWISE STATED.  
REMOVE ALL BURRS AND SHARP EDGES.  
FOR EXPLANATION OF NOTES, SYMBOLS  
ETC, SEE BS 308.

DRAWN	DATE	APPROVED	SCALE
Liubo	2021.04.17	Ludovic	1:1

HUNT & MITTON VALVE COMPANY

VALVE CODE		8801 SERIES
TITLE		G.A.:DN150(6") CAST STEEL GLOBE VALVE BELLOWS SEAL FOR USE ON CHLORINE FLANGED PN16 RF
DRG. No.	SHEET	OF
DN150_8801_PN16RF_1_LCC_C276_31803_EC	REV 1	